



EARTH DRILL ML RANGE



DEDICATED MINI LOADER EARTH DRILLS

The Earth Drills ML1500-ML2500 are the perfect choice for Mini Loaders. And, just like all planetary drives in our line up they are highly engineered and built to last.

HIGH QUALITY HYDRAULIC MOTORS


Auger Torque's huge buying power means we work closely with high quality suppliers to develop the most reliable attachments available on the market today.

NON-DISLODGE MENT SHAFT

Unique to Auger Torque, the Non-Dislodgement Shaft is a single piece drive shaft assembled top down and locked into the Earth Drill housing. This design guarantees that the shaft will never fall out, making for a safer work environment, not only for the operator but also any surrounding workers, a **MUST-HAVE FEATURE** for any safety conscious company.

EPICYCLIC GEARBOX

Torque is amplified by using the unique Auger Torque planetary gearbox. This system allows the motors output torque to be multiplied with extreme efficiency as well as ensuring the durability and reliability you need.



Visit the Auger Torque website to watch a demo

EARTHWORM ATTACHMENTS

0508 21 22 23

AUCKLAND: 211 ROSCOMMON RD, WIRI 2104

CHRISTCHURCH: 7 WASHBOURNES ROAD, WIGRAM, CHRISTCHURCH, 8042

SOUTHLAND: 1A HYDE ST, GORE 9710

www.augertorque.co.nz

EARTH DRILL – ML RANGE

Features

- ▶ Unique Auger Torque planetary gearbox offering high efficiency and extreme durability
- ▶ Single piece drive shaft
- ▶ Bearings fitted 50% larger than competitors
- ▶ Heavy duty steel construction
- ▶ Auger Torque's industry leading warranty
- ▶ Compatible with Auger Torques range of Alignment and Torque Monitoring products for **accurate earth drilling applications.**

Applications

- ▶ Fencing
- ▶ Landscaping
- ▶ Tree Planting
- ▶ Pole and mast installations
- ▶ Road Signage

Specifications



Model		ML1500	ML2000	ML2500
Torque Range	Nm	511-1496	639-2190	830-2847
	ft-lb	377-1103	471-1615	612-2100
Oil Pressure Range	Bar	70-205	70-240	70-240
	psi	1015-2973	1015-3481	1015-3481
Oil Flow Range	lpm	20-45	25-57	27-65
	gpm	5-13	7-15	7-17
Speed Range	rpm	44-98	43-99	36-87
Unit Height	mm	406	465	465
	inch	16	18	18
Unit Width	mm	205	205	205
	inch	8	8	8
Unit Weight	kg	38	40	40
	lb	80	86	86
Output Shaft Std (adaptors available)	inch	2.5	2.5	2.5
Drilling Performance				
Auger Series		S4	S4	S4
Auger Diameter	mm	100-400	100-450	100-500
	inch	4-16	4-6	4-20
Drilling Depth*	m	2-1	2.2-1	2.5-1.3
	ft	7-3	7-3	8-4

*Dependent on ground type

MOUNTING FRAME



2-Way Swing



4-Way Swing



Part of the Auger Torque Earthmoving range

EARTH DRILLS | AUGERS & WEAR PARTS | MAST-BASED DRILLING RIG | TRENCHERS | HAMMERS

EARTHWORM ATTACHMENTS

0508 21 22 23 | AUCKLAND: 211 ROSCOMMON RD, WIRI 2104 | CHRISTCHURCH: 7 WASHBOURNES ROAD, WIGRAM, CHRISTCHURCH, 8042 | SOUTHLAND: 1A HYDE ST, GORE 9710

www.augertorque.co.nz