

HEDGE TRIMMER



Auger Torque T150 Hedge Trimmer for Excavator and Skidsteer

The **Auger Torque Hedge Trimmer** is the perfect addition for excavators (1.5 – 8T) and skidsteer loaders, and offers a variety of motor sizes to suit your application. Attaching to an excavator provides extra-long cutting reach, gaining access to those taller trees and deeper hedges. The newly designed skidsteer mounting frame allows you to quickly switch the Hedge Trimmer between left and right sides of the skidsteer. The Hedge Trimmer is also ideal for cutting long grass and brush.

Attaching the optional tooth extension bar provides a full 2.5m cutting length. This is sure to make trimming more precise, efficient and will provide yet another way to expand the versatility of existing machines.

A neat and accurate cut, every time.



Features

- 1.5m cutting length
- Optional 1m cutting extension bar
- Cuts up to 40mm diameter
- Replace individual cutting teeth as required
- Hoses included
- Delivered ready to use

Visit the Auger Torque website to watch a demo

EARTHWORM ATTACHMENTS

www.augertorque.co.nz

Specifications

T150 HEDGE TRIMMER

50cc Motor Variant Suited to: Excavators 1.5-2.5 T Skidsteer Loaders Oil Pressure Range: 150-220 Bar (2176-3191 psi) Oil Flow Range: 30-48 lpm (7.9-12.7 gpm) Max. Cutting Diameter: 25 mm (0.98")

80cc Motor Variant Suited to:

Oil Pressure Range:

Oil Flow Range:

Excavators 2.5-4.5 T Skidsteer Loaders 150-220 Bar (2176-3191 psi) 40-68 lpm (10.6-18.0 gpm) Max. Cutting Diameter: 40 mm (1.58")

100cc Motor Variant Suited to:

Oil Pressure Range: Oil Flow Range: Max. Cutting Diameter: 40 mm (1.58")

Excavators 4.5-8 T **Skidsteer Loaders** 150-220 Bar (2176-3191 psi) 50-71 lpm (13.2-18.8 gpm)

Max. Back Pressure: 20 Bar (290 psi) Hose Port Diameter: 1/2" BSP Cutting Length: 1500 mm (59")

Dimensions (h x w x l): 203 mm x 270 mm x 1537 mm (7.99" x 10.61" x 60.5")

Weight:

69 kg (152 lb)

Hydraulic requirements

The Hedge Trimmer attachment needs an absolute minimum of 30Lpm to the attachment at all times to cut a maximum of 25mm diameter foliage, it will need at least 40Lpm to effectively cut up to 40mm diameter foliage.



Part of the Auger Torque landscaping range STUMP PLANERS | LOG SPLITTERS | MULCHERS | HEDGE TRIMMERS | SWEEPER BROOMS

EXTENSION

Cutting Length: Combined Cutting Length: Max. Cutting Diameter: (dependent on motor variant)

1 m (40") 2.5 m (100") 40 mm (1.58")

Dimensions (h x w x l): 118 mm x 1192 mm x 225 mm [4.65" x 46.93" x 8.86"]


Weight:

26 kg (57.3 lb)

OFFSET MOUNT

Max. Offset Distance: 1.3 m (51") Cutting Angle: Horizontal thru Vertical **Operating Voltage:** 12V Dimensions $(h \times w \times l)$: 420 mm x 245 mm x 1510 mm (16.46" x 9.69" x 59.33")

Weight:



www.augertorque.co.nz

EARTHWORM ATTACHMENTS

0508 21 22 23 AUCKLAND: 211 ROSCOMMON RD, WIRI 2104 CHRISTCHURCH: 7 WASHBOURNES ROAD, WIGRAM, CHRISTCHURCH, 8042 SOUTHLAND: 1A HYDE ST, GORE 9710